

**ANCHOR BOLTS**

SEAL ANCHOR BOLTS AT 48 IN O.C. AT  
SHEAR WALLS AND SHEAR WALL  
SCHEDULE (U.N.O.)  
AS A REPAIR FOR MISSING ANCHOR BOLTS  
5/8-IN. THREADED ROD ANCHORS MAY BE  
USED. THE ANCHOR SHALL BE EMBEDDED  
A MINIMUM 4' IN IN TO THE CONCRETE  
AND SHALL BE INSTALLED WITH AN EPOXY  
EDGE. THE ANCHOR SHALL BE FASTENED TO  
THE CONCRETE WITH SIMPSON EPOXY-SET™  
ADHESIVE AND INSTALLED IN ACCORDANCE  
WITH MANUFACTURER'S RECOMMENDATIONS.  
(CCESR - 288)

FOUNDATION SILLS SHALL BE BOLTED TO  
THE FOUNDATION OR FOUNDATION WALL  
AT 48 IN O.C. AND BRACKETED WITH  
SIMPSON WISA ANCHORS MAY BE USED TO  
REPLACE ANCHOR BOLTS AT ALL LOCATIONS  
EXCEPT SHEAR WALLS (CCESR - 285S)

FOUNDATION SILLS AT INTERIOR WALLS MAY  
USE SHOT-PINS FOR CONNECTION TO THE SLAB.  
PLATES SHALL HAVE A MIN. OF TWO BOLTS  
17' OF EACH END  
SHEAR WALL SILLS PLATES SHALL BE BOLTED  
TO THE FOUNDATION  
ALL ANCHOR BOLTS SHALL HAVE APPROX 20'  
PLATE WASHERS. THE HOLE IN THE PLATE  
WASHER IS PERMITTED TO BE DIAGONALLY  
SLOTTED WITH A WIDTH OF UP TO 3/16" LARGER  
NOT TO EXCEED 1/8" PROVIDED A STANDARD  
CUT WASHER IS PLACED BETWEEN THE PLATE  
WASHER AND THE NUT.

**GENERAL NOTES**

VERIFY ALL FLAT WORK WITH DEVELOPER  
PRIOR TO INSTALLATION.

**SHOT-PINS**

SHOT-PINS: 0.145 IN DIA. X 2.1/2 IN. LONG  
RANGEI REDHEAD (CCESR-T78) OR EQUAL,  
EXCEPT FOR SHEAR WALLS, INTERIOR WALLS  
AND FOUNDATION WALLS. THE SPACING SHALL  
FOLLOWS:


SPACING:  
BEARING WALLS: 16 IN O.C.  
NON-BEARING WALLS: 48 IN O.C.

**FOUNDATION NOTES**

1. SLAB REINFORCEMENT TO BE LOCATED MID-SLAB
2. MAX. WATER-CEMENT RATIO OF .50 REQ'D FOR  
SLAB CONCRETE
3. SUBMIT PROPOSED CONCRETE STRENGTH AS FOLLOWS:  
F<sub>c</sub> = 2800 PSI (FOOTINGS)  
F<sub>c</sub> = 3000 PSI (SLABS)
4. ALL SHEAR WALL ANCHOR BOLTS ARE  
TO BE 5/8" DIA. MINIMUM.
5. WHERE 3X SILLS OCCUR USE SIMPSON  
STRBL STAB BOLTS FOR HOLD-DOWNS.

**SHEAR ALL NEW WALLS**

ALL NEW EXTERIOR WALLS SHALL BE SHEATHED  
WITH 3/8" OSB WALLED WITH R4 COMMON WALLS  
AT 8' O.C. EDGE, 12' O.C. FIELD



**FOUNDATION PLAN**

<b>S1.1</b>	REVISIONS		RICHLAND HOUSING YUBA CITY, CA	November 16, 2016 
	NO.	DATE		
PROJECT MANAGER RICK ROBERTSON DIRECTOR RMR		1ST PLAN SUBMITTAL		
SCALE 1/4"=1'-0" CONST. SET ISSUED		JOB NO. 215230		
SHEET		SHEET		

**Robertson Engineering**

3111 FITE CIRCLE, #101B  
 SACRAMENTO, CALI FORNI A 95827  
 Phone: 916-363-7021 Fax: 916-363-7027

**ANCHOR BOLTS**

SEE ANCHOR BOLTS AT 8' ON C.C. AT SHEAR WALLS PER SCHEDULE (UNO) AS A REPAIR FOR MISSING ANCHOR BOLTS 8# IN THREADED ROD ANCHORS MAY BE USED. THE ANCHOR SHALL BE EMBEDDED A MINIMUM 4" IN THE CONCRETE AND THE ANCHOR SHALL BE FASTENED TO THE CONCRETE WITH SIMPSON EPOXY-SET ADHESIVE AND INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. (ICC ESR - 2598)

FOUNDATION SILL SHALL BE BOLTED TO THE FOUNDATION OR FOUNDATION WALL FOUNDATIONS AND GARAGE PERIMETER FOUNDATIONS. SIMPSON WASHA ANCHORS MAY BE USED TO REPLACE ANCHOR BOLTS AT ALL LOCATIONS EXCEPT SHEAR WALLS (ICC ESR - 2559) FOUNDATION SILL AT INTERIOR WALLS MAY USE SHOT PINS FOR CONNECTION TO THE SLAB. SHOT PINS SHALL HAVE MIN. OF TWO BOLTS PER SPACING ON ONE BOLT LOCATED WITHIN 1/2" OF EACH END. SHEAR WALL SILL PLATES SHALL BE BOLTED TO THE FOUNDATION. ALL ANCHOR BOLTS SHALL HAVE 3/8"x2 1/2" PLATE WASHERS. THE HOLE IN THE PLATE WASHERS IS PERMITTED TO BE DIAGONALLY SLOTTED WITH A WIDTH OF UP TO 3/8" LARGER THAN THE BOLT. THE BOLT SHALL NOT BE CIRCLED 1/4" PROVIDED A STANDARD CUT WASHER IS PLACED BETWEEN THE PLATE WASHER AND THE NUT.

**GENERAL NOTES**

VERIFY ALL ELEV WORK WITH DEVELOPER PRIOR TO INSTALLATION.

**SHOT PINS**

SHOT PINS: 0.45-IN. DIA X 2.12-IN. LONG (RANGE/REHEAD (ICC ESR-1799 OR EQUAL), EXCEPT FOR SHEAR WALLS, INTERIOR WALLS AND FOUNDATION WALLS. SPACING SHALL BE AS FOLLOWS:


SPACING:  
BEARING WALLS: 16 IN. O.C.  
NON-BEARING WALLS: 48 IN. O.C.

**FOUNDATION NOTES**

1. SLAB REINFORCEMENT TO BE LOCATED MID-SLAB
2. MAX. WATER-CEMENT RATIO OF .50 RECD FOR SLAB-ON-GRADE CONCRETE
3. MINIMUM CONCRETE COMPRESSIVE STRENGTHS AS FOLLOWS:  
F<sub>c</sub> = 2500 PSI. (FOOTINGS)  
F<sub>c</sub> = 3000 PSI. (SLABS)
4. ALL SHEAR WALL ANCHOR BOLTS ARE TO BE 8# DIA. MINIMUM.
5. WHERE X SILL PLATES OCCUR USE SIMPSON SSTBL STAB BOLTS FOR HOLD-DOWNS.

**SHEAR ALL NEW WALLS**

ALL NEW EXTERIOR WALLS SHALL BE SHEATHED WITH 3/8" OSB NAILED WITH 8# COMMON NAILS AT 8" O.C. EDGE, 12" O.C. FIELD



**UNIT C FOUNDATION**

SCALE: 1/4"=1'-0"

**FOUNDATION PLAN**

<p>NOVEMBER 16, 2016</p> <p><i>Robertson Engineering</i></p>		<p>RICHLAND HOUSING YUBA CITY, CA</p>													
<p>REVISIONS</p> <table border="1"> <thead> <tr> <th>NO.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		NO.	DATE	DESCRIPTION										<p>1ST PLAN SUBMITTAL</p> <p>SCALE: 1/4"=1'-0"</p> <p>CONST. SET ISSUED</p> <p>JOB NO. 215230</p> <p>SHEET S1.2</p>	
NO.	DATE	DESCRIPTION													
<p>PROJECT MANAGER RICK ROBERTSON</p> <p>DRAWN BY RMR</p>		<p>PROJECT MANAGER RICK ROBERTSON</p> <p>DRAWN BY RMR</p>													

**Robertson Engineering**  
 3111 FITE CIRCLE, #101B  
 SACRAMENTO, CALI FORNI A 95827  
 Phone: 916-363-7021 Fax: 916-363-7027

**STRUCTURAL LUMBER SPECS. (U.N.O.)**

1. 2X 4X BEAMS, HEADERS, AND POSTS:
2. 4X BEAMS, HEADERS AND POSTS:
3. 2X JOISTS AND RAFTERS:
4. 2X STUDS (MAX. 10 FT LONG):
5. 2X BR'S TO GRADE AND BETTER
6. 2X BR'S TO GRADE AND BETTER
7. 2X BR'S TO GRADE AND BETTER
8. 2X BR'S TO GRADE AND BETTER
9. 2X BR'S TO GRADE AND BETTER
10. 2X BR'S TO GRADE AND BETTER
11. 2X BR'S TO GRADE AND BETTER
12. 2X BR'S TO GRADE AND BETTER
13. 2X BR'S TO GRADE AND BETTER
14. 2X BR'S TO GRADE AND BETTER
15. 2X BR'S TO GRADE AND BETTER
16. 2X BR'S TO GRADE AND BETTER
17. 2X BR'S TO GRADE AND BETTER
18. 2X BR'S TO GRADE AND BETTER
19. 2X BR'S TO GRADE AND BETTER
20. 2X BR'S TO GRADE AND BETTER
21. 2X BR'S TO GRADE AND BETTER
22. 2X BR'S TO GRADE AND BETTER
23. 2X BR'S TO GRADE AND BETTER
24. 2X BR'S TO GRADE AND BETTER
25. 2X BR'S TO GRADE AND BETTER
26. 2X BR'S TO GRADE AND BETTER
27. 2X BR'S TO GRADE AND BETTER
28. 2X BR'S TO GRADE AND BETTER
29. 2X BR'S TO GRADE AND BETTER
30. 2X BR'S TO GRADE AND BETTER
31. 2X BR'S TO GRADE AND BETTER
32. 2X BR'S TO GRADE AND BETTER
33. 2X BR'S TO GRADE AND BETTER
34. 2X BR'S TO GRADE AND BETTER
35. 2X BR'S TO GRADE AND BETTER
36. 2X BR'S TO GRADE AND BETTER
37. 2X BR'S TO GRADE AND BETTER
38. 2X BR'S TO GRADE AND BETTER
39. 2X BR'S TO GRADE AND BETTER
40. 2X BR'S TO GRADE AND BETTER
41. 2X BR'S TO GRADE AND BETTER
42. 2X BR'S TO GRADE AND BETTER
43. 2X BR'S TO GRADE AND BETTER
44. 2X BR'S TO GRADE AND BETTER
45. 2X BR'S TO GRADE AND BETTER
46. 2X BR'S TO GRADE AND BETTER
47. 2X BR'S TO GRADE AND BETTER
48. 2X BR'S TO GRADE AND BETTER
49. 2X BR'S TO GRADE AND BETTER
50. 2X BR'S TO GRADE AND BETTER
51. 2X BR'S TO GRADE AND BETTER
52. 2X BR'S TO GRADE AND BETTER
53. 2X BR'S TO GRADE AND BETTER
54. 2X BR'S TO GRADE AND BETTER
55. 2X BR'S TO GRADE AND BETTER
56. 2X BR'S TO GRADE AND BETTER
57. 2X BR'S TO GRADE AND BETTER
58. 2X BR'S TO GRADE AND BETTER
59. 2X BR'S TO GRADE AND BETTER
60. 2X BR'S TO GRADE AND BETTER
61. 2X BR'S TO GRADE AND BETTER
62. 2X BR'S TO GRADE AND BETTER
63. 2X BR'S TO GRADE AND BETTER
64. 2X BR'S TO GRADE AND BETTER
65. 2X BR'S TO GRADE AND BETTER
66. 2X BR'S TO GRADE AND BETTER
67. 2X BR'S TO GRADE AND BETTER
68. 2X BR'S TO GRADE AND BETTER
69. 2X BR'S TO GRADE AND BETTER
70. 2X BR'S TO GRADE AND BETTER
71. 2X BR'S TO GRADE AND BETTER
72. 2X BR'S TO GRADE AND BETTER
73. 2X BR'S TO GRADE AND BETTER
74. 2X BR'S TO GRADE AND BETTER
75. 2X BR'S TO GRADE AND BETTER
76. 2X BR'S TO GRADE AND BETTER
77. 2X BR'S TO GRADE AND BETTER
78. 2X BR'S TO GRADE AND BETTER
79. 2X BR'S TO GRADE AND BETTER
80. 2X BR'S TO GRADE AND BETTER
81. 2X BR'S TO GRADE AND BETTER
82. 2X BR'S TO GRADE AND BETTER
83. 2X BR'S TO GRADE AND BETTER
84. 2X BR'S TO GRADE AND BETTER
85. 2X BR'S TO GRADE AND BETTER
86. 2X BR'S TO GRADE AND BETTER
87. 2X BR'S TO GRADE AND BETTER
88. 2X BR'S TO GRADE AND BETTER
89. 2X BR'S TO GRADE AND BETTER
90. 2X BR'S TO GRADE AND BETTER
91. 2X BR'S TO GRADE AND BETTER
92. 2X BR'S TO GRADE AND BETTER
93. 2X BR'S TO GRADE AND BETTER
94. 2X BR'S TO GRADE AND BETTER
95. 2X BR'S TO GRADE AND BETTER
96. 2X BR'S TO GRADE AND BETTER
97. 2X BR'S TO GRADE AND BETTER
98. 2X BR'S TO GRADE AND BETTER
99. 2X BR'S TO GRADE AND BETTER
100. 2X BR'S TO GRADE AND BETTER


**SHEAR ALL NEW WALLS**

ALL NEW EXTERIOR WALLS SHALL BE SHEATHED WITH 5/8" OSB NAILLED WITH 8d COMMON WALLS AT 12" O.C. EDGES 12" O.C. FIELD.


**ROOF SHEATHING**

1/2" N. OSB (240) PLYWOOD OR EQUIVALENT SHALL BE USED FOR ROOF SHEATHING PERPENDICULAR TO FRAMING. USE CXX OR EQUIVALENT AT OVERHANGS OR WHERE EXPOSED.

WALL WITH 8d's COMMON 8" N. O.C. AT EDGES AND BOUNDARY, 12" N. O.C. AT FIELD.



SCALE 1/4"=1'-0"



SCALE 1/4"=1'-0"

**LOW ROOF FRAMING**

**Robertson Engineering**  
 3111 FITE CIRCLE, #101B  
 SACRAMENTO, CALI FORNI A 95827  
 Phone: 916-363-7021 Fax: 916-363-7027

November 16, 2016

**REVISIONS**

NO.	DATE	DESCRIPTION

**RICHLAND HOUSING**  
YUBA CITY, CA

**S2.1**

1ST PLAN SUBMITTAL  
 SCALE 1/4"=1'-0"  
 CONST. SET ISSUED  
 JOB NO. 215230  
 SHEET

**PROJECT MANAGER**  
RICK ROBERTSON  
**DRAFTER**  
RMR

THESE DOCUMENTS ARE THE PROPERTY OF ROBERTSON ENGINEERING. NO PART OF THESE DOCUMENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF ROBERTSON ENGINEERING.

**STRUCTURAL LUMBER SPECS. (U.N.O.)**


1. 2X 4X BEAMS, HEADERS, AND POSTS: DRY OR BETTER
2. 2X BEAMS, HEADERS AND POSTS: DRY OR BETTER
3. 2X JOISTS AND RAFTERS: DRY OR BETTER
4. 2X STUDS (MAX. 10 FT LONG): DRY OR BETTER
5. 2X STUDS (MAX. 9 FT LONG): DRY AND BETTER
6. 6/8, 2X-4/4 DPIPE 1600 FT RADIUS CAMBER.
7. ALL BEAMS SHALL BE STAINED, PAINTED OR OTHERWISE PROTECTED FROM EXPOSURE TO SEAMARK.

**SHEAR ALL NEW WALLS**

ALL NEW EXTERIOR WALLS SHALL BE SHEATHED WITH 5/8" OSB NAILLED WITH 8d COMMON NAILS AT 12" O.C. EDGE, 12" O.C. FIELD.

**ROOF SHEATHING**

1/2" N. OSB (240) PLYWOOD OR EQUIVALENT SHALL BE USED FOR ROOF SHEATHING PERPENDICULAR TO FRAMING. USE CEX OR EQUIVALENT AT OVERHANGS OR WHERE EXPOSED.  
WALL WITH 8d's (COMMON) 6 N. O.C. AT EDGES AND BOUNDARY, 12 N. O.C. AT FIELD.



**UNIT C FRAMING**

SCALE 1/4"=1'-0"

**LOW ROOF FRAMING**


<b>S2.2</b>	NOVEMBER 16, 2016		RICHLAND HOUSING YUBA CITY, CA
	REVISIONS NO.      DATE		
PROJECT MANAGER RICK ROBERTSON			
DRAFTER RMR			
1ST PLAN SUBMITTAL			
SCALE 1/4"=1'-0"			
CONST. SET ISSUED			
JOB NO. 215230			
SHEET			

*Robertson Engineering*

**3111 FITE CIRCLE, #101B**  
 SACRAMENTO, CALI FORNI A 95827  
 Phone: 916-363-7021 Fax: 916-363-7027





November 16, 2016  



**RICHLAND HOUSING**  
 YUBA CITY, CA

REVISIONS	
NO.	DATE

PROJECT MANAGER  
**RICK ROBERTSON**  
 DRAWER  
**RMK**  
 1ST PLAN SUBMITTAL

SCALE  
 N.T.S.  
 CONST. SET ISSUED  
 JOB NO.  
 215230  
 SHEET

**SD2**

	 <ol style="list-style-type: none"> <li>EXISTING BEARING WALL</li> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>2X6 LEDGER WITH (2) SWS</li> <li>1/4x4-1/2" WOOD SCREWS IN EACH STUD CLIP EACH RAFTER TO LEDGER</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>HEADER PER PLAN</li> <li>NOT USED</li> <li>H25T CLIP EACH RAFTER TO WALL</li> <li>TOP PLATE</li> <li>2X BLOTTING</li> <li>7x4x4 WOOD OR PER ARCH</li> <li>ACHT ELECTRICAL EAVE DETAIL</li> <li>AS5 CLIP EACH BLOCK TO WALL</li> <li>TOP PLATE</li> <li>CEILING JOISTS WHERE OCCURS</li> <li>WALL RAFTER TO CEILING JOISTS WITH 2-16# SINKERS U.N.O.</li> </ol>	<ol style="list-style-type: none"> <li>2X BEARING WALL - 16" O.C. STUD</li> <li>SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X P. 1" SILL PLATE AND PER SHEAR WALL SCHEDULE</li> <li>3X 10x29 PLATE WASHERS, 3/4" DIA. ANCHOR BOLTS W/ MIN. O.C. SPACING PER WALL SCHEDULE PER PLAN</li> <li>AT P3, P4, P5, &amp; P6 SHEAR WALLS ANCHOR BOLTS ARE TO BE PLACED SUCH THAT THE EDGE OF THE WASHER IS NOT MORE THAN 1" FROM THE FACE OF THE SHEATHING</li> <li>GARAGE SLAB PER PLAN</li> <li>#4 REBAR TOP AND BOTTOM</li> <li>FOOTING FOR EXTERIOR WAINSCOT WHERE OCCURS PER ARCH.</li> <li>ADDITIONAL #4 BAR IN STEM</li> </ol>	<ol style="list-style-type: none"> <li>PATIO SLAB</li> <li>BEARING POST PER PLAN</li> <li>POST BASE PER PLAN</li> <li>REBAR PER PLAN</li> </ol>
	<ol style="list-style-type: none"> <li>BEAM PER PLAN</li> <li>POST PER PLAN WALL</li> <li>PROTECT ON SEE STAIR DETAIL</li> <li>STRAP PER PLAN</li> <li>WALL TOP PLATE</li> <li>STRAP MAY BE INSTALLED TO THE SIDE OF THE BEAM AND WALL TOP PLATE AS AN ALTERNATE</li> <li>RAISED BEAM WHERE OCCURS</li> <li>AT RAISED BEAM CONDITION, WALL STRAP TO TOP OF WALL AND UNDERSIDE OF BEAM</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>H25T CLIP EACH RAFTER TO WALL</li> <li>TOP PLATE</li> <li>2X BLOTTING</li> <li>7x4x4 WOOD OR PER ARCH</li> <li>COX PL WOOD OR PER ARCH ELECTRICAL EAVE DETAIL</li> <li>AS5 CLIP EACH BLOCK TO WALL</li> <li>2X4 CEILING JOISTS AT 24" O.C. WHERE OCCURS</li> <li>WALL RAFTER TO CEILING JOISTS WITH 2-16# SINKERS U.N.O.</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>BEARING WALL 16" O.C. STUD SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X BARGE RAFTER OUTLOOKERS WITH 2-16# SINKERS INTO OUTLOOKERS</li> <li>MATCH RAFTER DEPT AT 48" O.C. U.N.O.</li> <li>4X2 OUTLOOKERS AT 48" O.C. INTO BLOTTING</li> <li>3x4# COMMONS AT 6" O.C. INTO BLOTTING</li> <li>AS5 CLIPS AT 24" O.C.</li> </ol>	<ol style="list-style-type: none"> <li>BEARING POST PER PLAN</li> <li>POST BASE PER PLAN</li> <li>REBAR PER PLAN</li> </ol>
<ol style="list-style-type: none"> <li>ROOF SHEATHING PER SHEET S2</li> <li>2X6 RAFTERS AT 24" O.C.</li> <li>2X6 RIDGE</li> <li>2X6 COLLARTIES AT 24" O.C.</li> <li>AS5 CLIP RAFTER TO RIDGE BEAM ALTERNATE SIDES OF RAFTERS TO RIDGE BEAM</li> <li>ROOF TRUSS WALLS WITH 6-16# SINKER WALLS</li> <li>2X10 LEDGER WITH 4-16# SINKERS IN EACH EXISTING STUD</li> <li>1/2" HANGER</li> <li>2X BLOTTING BETWEEN EXISTING STUDS</li> <li>16# SINKER WALLS INTO BLOTTING</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>BEARING WALL 16" O.C. STUD SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X BARGE RAFTER OUTLOOKERS WITH 2-16# SINKERS INTO OUTLOOKERS</li> <li>MATCH RAFTER DEPT AT 48" O.C. U.N.O.</li> <li>4X2 OUTLOOKERS AT 48" O.C. INTO BLOTTING</li> <li>3x4# COMMONS AT 6" O.C. INTO BLOTTING</li> <li>AS5 CLIPS AT 24" O.C.</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X BARGE RAFTER OUTLOOKERS WITH 2-16# SINKERS INTO OUTLOOKERS</li> <li>MATCH RAFTER DEPT AT 48" O.C. U.N.O.</li> <li>4X2 OUTLOOKERS AT 48" O.C. INTO BLOTTING</li> <li>3x4# COMMONS AT 6" O.C. INTO BLOTTING</li> <li>AS5 CLIPS AT 24" O.C.</li> </ol>	<ol style="list-style-type: none"> <li>EXISTING SLAB FOOTING</li> <li>NEW FOOTING</li> <li>NEW SLAB</li> <li>NEW SLAB FOOTING TO EXISTING WITH #4 REBAR PINS TOP AND BOTTOM, EMBED 6" INTO EXISTING WITH SIMPSON EPOXY-SET/EP ADHESIVE</li> <li>NEW STORAGE ROOM SLAB PER PLAN</li> <li>1/2" FOAM SPACER</li> </ol>	<ol style="list-style-type: none"> <li>EXISTING SLAB FOOTING</li> <li>NEW FOOTING</li> <li>NEW SLAB</li> <li>NEW SLAB FOOTING TO EXISTING WITH #4 REBAR PINS TOP AND BOTTOM, EMBED 6" INTO EXISTING WITH SIMPSON EPOXY-SET/EP ADHESIVE</li> <li>NEW STORAGE ROOM SLAB PER PLAN</li> <li>1/2" FOAM SPACER</li> </ol>
<ol style="list-style-type: none"> <li>EXISTING BEARING WALL</li> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>2X6 LEDGER WITH (2) SWS</li> <li>1/4x4-1/2" WOOD SCREWS IN EACH STUD CLIP EACH RAFTER TO LEDGER</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>BEARING WALL 16" O.C. STUD SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X BARGE RAFTER OUTLOOKERS WITH 2-16# SINKERS INTO OUTLOOKERS</li> <li>MATCH RAFTER DEPT AT 48" O.C. U.N.O.</li> <li>4X2 OUTLOOKERS AT 48" O.C. INTO BLOTTING</li> <li>3x4# COMMONS AT 6" O.C. INTO BLOTTING</li> <li>AS5 CLIPS AT 24" O.C.</li> </ol>	<ol style="list-style-type: none"> <li>ROOF SHEATHING PER PLAN</li> <li>RAFTERS PER PLAN</li> <li>SPACING U.N.O.</li> <li>WALL SHEATHING PER PLAN</li> <li>2X BARGE RAFTER OUTLOOKERS WITH 2-16# SINKERS INTO OUTLOOKERS</li> <li>MATCH RAFTER DEPT AT 48" O.C. U.N.O.</li> <li>4X2 OUTLOOKERS AT 48" O.C. INTO BLOTTING</li> <li>3x4# COMMONS AT 6" O.C. INTO BLOTTING</li> <li>AS5 CLIPS AT 24" O.C.</li> </ol>	<ol style="list-style-type: none"> <li>EXISTING SLAB FOOTING</li> <li>NEW FOOTING</li> <li>NEW SLAB</li> <li>NEW SLAB FOOTING TO EXISTING WITH #4 REBAR PINS TOP AND BOTTOM, EMBED 6" INTO EXISTING WITH SIMPSON EPOXY-SET/EP ADHESIVE</li> <li>NEW STORAGE ROOM SLAB PER PLAN</li> <li>1/2" FOAM SPACER</li> </ol>	<ol style="list-style-type: none"> <li>EXISTING SLAB FOOTING</li> <li>NEW FOOTING</li> <li>NEW SLAB</li> <li>NEW SLAB FOOTING TO EXISTING WITH #4 REBAR PINS TOP AND BOTTOM, EMBED 6" INTO EXISTING WITH SIMPSON EPOXY-SET/EP ADHESIVE</li> <li>NEW STORAGE ROOM SLAB PER PLAN</li> <li>1/2" FOAM SPACER</li> </ol>

REVISED ROOF DETAIL